



Magna Acryl coat

Description:

Magna Acryl coat is 100% acrylic latex paint for exterior use. Magna Acryl coat has a matte sheen, mildew resistant finish, perfect for extreme climatic conditions. Magna Acryl coat offers improved hiding for greater coverage and excellent color retention, the ultimate in durability. Magna Acryl coat is very easily applied with brush or roller and is ideally suitable for the decoration and protection of air-dried walls, fiber building boards, brick, masonry, stucco and cinder block.

Features:

Weather resistant properties.
Quick dry.

Recommended For:

Old and new Concrete.

Product Information

Technical Data	Magna Acryl coat
Vehicle Type	100% Acrylic
Pigment Type	Titanium Dioxide
Solids by Volume	47%
Theoretical Coverage At	
Recommended Film Thickness	23 m ² /US Gallon
<i>Depending on surface texture and porosity</i>	
Recommended Film Thickness	Dry 35µm
Dry Time @ 25°C	To Touch 4 Hour
	To Handle 6 Hours
	To Recoat 12 hours
Dries By	Evaporation
Flash Point	--
Gloss	Eggshell
Thin with	Water
Clean up Thinner	Water
Weight Per Gallon	5.67 kg/gallon

Limitation of liability:

The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Antilliaanse Verffabriek B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Antilliaanse Verffabriek B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Antilliaanse Verffabriek B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.

**Surface Preparation:**

Surface must be clean, free of dust, chalk, peeling paint and mildew. Remove loose paint by scraping, sanding or power washing. If mildew is present remove all traces with a solution of Ammonia. CAUTION: use protective clothing and work goggles when applying Ammonia solution. Repair all surface imperfections such as nail holes and cracks. New plaster must be allowed to cure (30-60 days). WARNING! Scraping or sanding of old paint may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS. PREGNANT WOMEN SHOULD AVOID EXPOSURE.

Application:

Stir paint thoroughly before and during use. Apply one or two coats for best results.

Clean Up:

Clean brushes and rollers with clean water after use. Spray equipment should be cleaned with water and given a final rinse with White Spirit.

Safety Information:

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application.

First Aid:

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Limitation of liability:

The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Antilliaanse Verffabriek B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Antilliaanse Verffabriek B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Antilliaanse Verffabriek B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.