



Pehalin Monovit

General Description:

Pehalin Monovit is a pigmented semi synthetic alkyd based paint for interior and exterior wood protection. Pehalin Monovit provides an excellent, durable semi permeable finish for wood.

Features:

Moisture regulating finish.
Elastic.

Recommended For:

Residential or commercial applications where a premium quality finish is desired.

Product Information

Technical Data		Pehalin Monovit
Vehicle Type		Semi Synthetic Alkyd
Pigment Type		Titanium Dioxide
Volume Solids		--
Theoretical Coverage At		
Recommended Film Thickness		49 m ² /US Gallon
<i>Depending on surface texture and porosity</i>		
Recommended Film Thickness	Dry	30µm
Dry Time @ 25°C	To Touch	6 Hours
	To Handle	8 Hours
	To Recoat	24 Hours
Dries By		Oxidation
Flash Point		--
Gloss		Semi Gloss
Thin with		White Spirit
Clean up Thinner		White Spirit
Weight Per Gallon		4.35 kg/gallon

Surface Preparation:

Surface must be clean, free of dust, grease, chalk and peeling paint. Remove loose paint by scraping, sanding or power washing. If mildew is present remove all traces with a solution of Ammonia. CAUTION: use protective clothing and work goggles when applying Ammonia solution. WARNING! Scraping or sanding of old paint may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS. PREGNANT WOMEN SHOULD AVOID EXPOSURE.

Limitation of liability:

The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Antilliaanse Verffabriek B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Antilliaanse Verffabriek B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Antilliaanse Verffabriek B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.

**Application:**

Stir paint thoroughly prior and during use.

Clean Up:

Clean brushes with White Spirit.

Safety Information:

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application. Ensure fresh air entry.

First Aid:

If you experience difficulty breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Limitation of liability:

The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Antilliaanse Verffabriek B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Antilliaanse Verffabriek B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Antilliaanse Verffabriek B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.